

Watch a video of this Sew Easy online
at FonsandPorter.com/CornerPop

SEWeasy™ Corner Pop Units

Use Deb Tucker's Corner Pop™ tool to make perfectly filled corners with less waste than the traditional diagonal seams method.

CUT AWAY CORNERS

1. Cut your base shape to the exact size required for your project. For *Pretty Posies*, the base is a 5" square (*Photo A*).
2. Choose the size you wish to cut away from a corner. The lines on the Corner Pop tool are the finished size of the replacement triangle. Place the corresponding Cut Away Corner line on the corner you wish to cut away, aligning raw edges of base unit with lines on Corner Pop tool. Trim corner of base unit. For *Pretty Posies*, 2 of the Cut Away Corners are 1½" and 1 Cut Away Corner is ¾" (*Photos B and C*).

REPLACEMENT CORNERS

1. Replacement triangles are cut slightly oversized. Cut a square that is 1¼" larger than the size you chose to cut away from base shape. Cut square in half diagonally to make 2 replacement triangles. For *Pretty Posies*, the squares used to make replacement triangles are cut 2¾" and 2" (*Photo D*).
2. With right sides facing, and raw edges aligned, center the replacement triangle on the trimmed corner of the base. Stitch using a ¼" seam allowance. Repeat for remaining Cut Away Corners using appropriate-size replacement triangle (*Photo E*).
3. Press seam allowances toward the base, toward the replacement triangle, or open (*Photo F*).
4. Trim excess replacement triangle fabric to complete unit. Place the diagonal line on the Corner Trim Down section of the Corner Pop tool that corresponds to your Cut Away size on the sewn seam, and align the cutting edges of the tool with the raw edges of the base shape. For *Pretty Posies*, the lines used are 1½" and ¾" (*Photos G and H*).

